

**FOR ANY AIRGUN HAVING .2mm PER CLICK
 REAR SIGHTS AT A DISTANCE OF 10 METERS,
 THE POINT OF IMPACT ON TARGET WILL
 CHANGE APPROX. .2 mm (1/128") PER CLICK.
 THE CHART BELOW SHOWS THE APPROX.
 NUMBER OF CLICKS (OF SIGHT ADJ. SCREWS)**

<u>VERTICAL OR HORIZONTAL DISTANCE OF SHOT FROM POINT OF AIM IN INCHES</u>	<u>NUMBER OF CLICKS REQUIRED</u>	<u>INSTRUCTIONS FOR THE DIRECTION OF ROTATION FOR MOST EUROPEAN MANUFACTURED PEEP SIGHTS</u>
1	127	<p><u>Shooting high:</u> ⇒Turn the upper adjusting screw into direction „H“.</p> <p><u>Shooting low:</u> ⇒Turn the upper adjusting screw into direction „T“.</p> <p><u>Shooting right:</u> ⇒Turn the side adjusting screw into direction „R“.</p> <p><u>Shooting left:</u> ⇒Turn the side adjusting screw into direction „L“.</p>
15/16	119	
7/8	111	
13/16	103	
3/4	95	
11/16	87	
5/8	79	
9/16	71	
1/2	64	
7/16	56	
3/8	48	
5/16	40	
1/4	32	
3/16	24	
1/8	16	
1/16	8	
1/32	4	
1/64	2	
1/128	1	